

CUTTING OIL 5 LITRE

Version 2.9 Revision Date: 06.05.2020 SDS Number: 737012-00004 Date of last issue: 08.10.2019
Date of first issue: 18.07.2012

Section 1: Identification

Product name : CUTTING OIL 5 LITRE

Product code : 0893 050 1

Manufacturer or supplier's details

Company : Wurth NewZealand Ltd

Address : 42 Hobill Ave
Manukau City 2104

Telephone : +64 9 262 3040

Emergency telephone number : 0800 764 766

E-mail address : prodsafe@wuerth.com

Telefax : +64 9 262 3030

Recommended use of the chemical and restrictions on use

Recommended use : Anti-friction agent and lubricant

Section 2: Hazard identification**GHS Classification**

Flammable liquids : Category 2

Skin corrosion/irritation : Category 2

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.

Precautionary statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.

CUTTING OIL 5 LITRE

Version	Revision Date:	SDS Number:	Date of last issue: 08.10.2019
2.9	06.05.2020	737012-00004	Date of first issue: 18.07.2012

P233 Keep container tightly closed.
 P241 Use explosion-proof electrical/ ventilating/ lighting equip-
 ment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P264 Wash skin thoroughly after handling.
 P280 Wear protective gloves/ protective clothing/ eye protec-
 tion/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON
 CENTER or doctor/ physician.
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off
 immediately all contaminated clothing. Rinse skin with water/
 shower.
 P331 Do NOT induce vomiting.
 P332 + P313 If skin irritation occurs: Get medical advice/ atten-
 tion.
 P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste
 disposal plant.

Other hazards which do not result in classification

Vapours may form explosive mixture with air.

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture
 Chemical nature : Hydrocarbons

Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	>= 60 -<= 100
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	92128-66-0	>= 10 -< 20

Alternative CAS Numbers for some regions

Chemical name	Alternative CAS Number(s)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	64742-49-0

Section 4: First-aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-
 vice immediately.

CUTTING OIL 5 LITRE

Version	Revision Date:	SDS Number:	Date of last issue: 08.10.2019
2.9	06.05.2020	737012-00004	Date of first issue: 18.07.2012

- When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control centre immediately.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Causes skin irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

Section 5: Fire-fighting measures

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do

CUTTING OIL 5 LITRE

Version	Revision Date:	SDS Number:	Date of last issue: 08.10.2019
2.9	06.05.2020	737012-00004	Date of first issue: 18.07.2012

so.
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Hazchem Code : 3YE

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

Section 7: Handling and storage

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Avoid inhalation of vapour or mist.
Do not swallow.

CUTTING OIL 5 LITRE

Version	Revision Date:	SDS Number:	Date of last issue: 08.10.2019
2.9	06.05.2020	737012-00004	Date of first issue: 18.07.2012

Avoid contact with eyes.
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
 Non-sparking tools should be used.
 Keep container tightly closed.
 Keep away from heat and sources of ignition.
 Take precautionary measures against static discharges.
 Take care to prevent spills, waste and minimize release to the environment.

- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
 When using do not eat, drink or smoke.
 Wash contaminated clothing before re-use.
- Conditions for safe storage : Keep in properly labelled containers.
 Store locked up.
 Keep tightly closed.
 Keep in a cool, well-ventilated place.
 Store in accordance with the particular national regulations.
 Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:
 Self-reactive substances and mixtures
 Organic peroxides
 Oxidizing agents
 Flammable gases
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Poisonous gases
 Explosives

Section 8: Exposure controls/personal protection
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	WES-TWA (Mist)	5 mg/m ³	NZ OEL
	Further information: Sampled by a method that does not collect vapour.			
		WES-STEL (Mist)	10 mg/m ³	NZ OEL
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	92128-66-0	WES-TWA	300 ppm 890 mg/m ³	NZ OEL
		WES-STEL	500 ppm 1,480 mg/m ³	NZ OEL
		WES-TWA	5 mg/m ³	NZ OEL

CUTTING OIL 5 LITRE

Version Revision Date: SDS Number: Date of last issue: 08.10.2019
 2.9 06.05.2020 737012-00004 Date of first issue: 18.07.2012

		(Mist)		
	Further information: Sampled by a method that does not collect vapour.			
		WES-STEL (Mist)	10 mg/m ³	NZ OEL

Engineering measures : Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapour type

Hand protection

Material : Nitrile rubber
 Break through time : > 480 min
 Glove thickness : >= 0.5 mm
 Protective index : Class 6

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
 Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
 Wear the following personal protective equipment:
 If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
 Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Section 9: Physical and chemical properties

Appearance : liquid

Colour : tan

CUTTING OIL 5 LITRE

Version Revision Date: SDS Number: Date of last issue: 08.10.2019
2.9 06.05.2020 737012-00004 Date of first issue: 18.07.2012

Odour : characteristic

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : 78 °C

Flash point : -9 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper flammability limit : 7.0 %(V)

Lower explosion limit / Lower flammability limit : 0.6 %(V)

Vapour pressure : 58.5 hPa (20 °C)

Relative vapour density : No data available

Density : 0.82 g/cm³ (20 °C)

Solubility(ies)
 Water solubility : immiscible

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity
 Viscosity, dynamic : 3.5 mPa.s (40 °C)

 Viscosity, kinematic : No data available

Explosive properties : Not explosive

CUTTING OIL 5 LITRE

Version	Revision Date:	SDS Number:	Date of last issue: 08.10.2019
2.9	06.05.2020	737012-00004	Date of first issue: 18.07.2012

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

Section 10: Stability and reactivity

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Highly flammable liquid and vapour.
Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

Section 11: Toxicological information

Exposure routes : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy paraffinic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

CUTTING OIL 5 LITRE

Version 2.9 Revision Date: 06.05.2020 SDS Number: 737012-00004 Date of last issue: 08.10.2019
Date of first issue: 18.07.2012

Acute inhalation toxicity : LC50 (Rat): > 5.61 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:**Distillates (petroleum), hydrotreated heavy paraffinic:**

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy paraffinic:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy paraffinic:**

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

CUTTING OIL 5 LITRE

Version 2.9 Revision Date: 06.05.2020 SDS Number: 737012-00004 Date of last issue: 08.10.2019
Date of first issue: 18.07.2012

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Chronic toxicity**Germ cell mutagenicity**

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy paraffinic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (vapour)
Method: OPPTS 870.5395
Result: negative

Carcinogenicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy paraffinic:**

Species : Mouse
Application Route : Skin contact
Exposure time : 78 weeks
Method : OECD Test Guideline 451
Result : negative
Remarks : Based on data from similar materials

CUTTING OIL 5 LITRE

Version 2.9 Revision Date: 06.05.2020 SDS Number: 737012-00004 Date of last issue: 08.10.2019
Date of first issue: 18.07.2012

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Mouse
Application Route : Skin contact
Exposure time : 102 weeks
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated heavy paraffinic:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

STOT - single exposure

Not classified based on available information.

Components:**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity**Components:****Distillates (petroleum), hydrotreated heavy paraffinic:**

CUTTING OIL 5 LITRE

Version 2.9 Revision Date: 06.05.2020 SDS Number: 737012-00004 Date of last issue: 08.10.2019
Date of first issue: 18.07.2012

Species : Rabbit
NOAEL : 1,000 mg/kg
Application Route : Skin contact
Exposure time : 4 Weeks
Method : OECD Test Guideline 410
Remarks : Based on data from similar materials

Species : Rat
NOAEL : > 980 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 4 Weeks

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rat
NOAEL : > 20 mg/l
Application Route : inhalation (vapour)
Exposure time : 13 Weeks

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Components:**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Section 12: Ecological information**Ecotoxicity****Components:****Distillates (petroleum), hydrotreated heavy paraffinic:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

CUTTING OIL 5 LITRE

Version 2.9 Revision Date: 06.05.2020 SDS Number: 737012-00004 Date of last issue: 08.10.2019
Date of first issue: 18.07.2012

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.5 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 2.6 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Persistence and degradability**Components:****Distillates (petroleum), hydrotreated heavy paraffinic:**

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

CUTTING OIL 5 LITRE

Version	Revision Date:	SDS Number:	Date of last issue: 08.10.2019
2.9	06.05.2020	737012-00004	Date of first issue: 18.07.2012

Biodegradation: 77.05 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Bioaccumulative potential**Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Partition coefficient: n- : log Pow: 4
octanol/water Remarks: Based on data from similar materials

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

Section 14: Transport information**International Regulations****UNRTDG**

UN number : UN 3295
Proper shipping name : HYDROCARBONS, LIQUID, N.O.S.
Class : 3
Packing group : II
Labels : 3

IATA-DGR

UN/ID No. : UN 3295
Proper shipping name : Hydrocarbons, liquid, n.o.s.
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo : 364
aircraft)
Packing instruction (passen- : 353
ger aircraft)

CUTTING OIL 5 LITRE

Version	Revision Date:	SDS Number:	Date of last issue: 08.10.2019
2.9	06.05.2020	737012-00004	Date of first issue: 18.07.2012

IMDG-Code

UN number	:	UN 3295
Proper shipping name	:	HYDROCARBONS, LIQUID, N.O.S.
Class	:	3
Packing group	:	II
Labels	:	3
EmS Code	:	F-E, S-D
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**NZS 5433**

UN number	:	UN 3295
Proper shipping name	:	HYDROCARBONS, LIQUID, N.O.S.
Class	:	3
Packing group	:	II
Labels	:	3
Hazchem Code	:	3YE

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture****HSNO Approval Number**

HSR002603 Lubricants Flammable Group Standard 2017

HSW Controls

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

NZIoC	:	All ingredients listed or exempt.
-------	---	-----------------------------------

Section 16: Other information**Further information**

Sources of key data used to compile the Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
---	---	---

CUTTING OIL 5 LITRE

Version	Revision Date:	SDS Number:	Date of last issue: 08.10.2019
2.9	06.05.2020	737012-00004	Date of first issue: 18.07.2012

Date format : dd.mm.yyyy

Full text of other abbreviations

NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average

NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

NZ / EN