

MATERIAL SAFETY DATA SHEET
Title: LIQUEFIED PETROLEUM GAS MATERIAL SAFETY DATA SHEET
Date of Issue: 1 October 2021
Date of Next Review: 1 October 2026

MATERIAL SAFETY DATA SHEET LIQUEFIED PETROLEUM GAS



IDENTIFICATION:

Chemical Name: Liquid Petroleum Gas

Synonyms: LPG

UN Number: 1075

Use: Heating, and cutting gas.

HAZARDS IDENTIFICATION:

Dangerous Goods Class and Subsidiary Risk: 2.1

HSNO Classification: 2.1.1A

Hazard Statement:

Extremely flammable gas.

Explosive, fire, blast or projectile hazard.

Precautionary Statements:

Read label before use.

Read Safety Data Sheet before use.

Protect from heat, sparks, open flames, hot surfaces and all other ignition sources

No Smoking

Store in a well-ventilated place.

Wear protective gloves and eye protection.

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Eliminate all ignition sources if safe to do so.

Store in a well-ventilated place.

Do not subject to any rough handling (grinding/shock/friction/banging).

Explosion risk in case of fire.

Fight fire with normal precautions from a reasonable distance.

Take precautionary measures against static discharges.

Wear Protective Gloves and Eye protection.

MATERIAL SAFETY DATA SHEET

Title: **LIQUEFIED PETROLEUM GAS MATERIAL SAFETY DATA SHEET**

Date of Issue: 1 October 2021

Date of Next Review: 1 October 2026

COMPOSITION / INGREDIENTS:

Chemical Entity	CAS Number	Proportion
Liquefied Petroleum Gas	68476-85-7	100%

Contains no other components or impurities that will influence the classification of the product.

FIRST AID MEASURES:

Health Effects

Swallowed: Not applicable due to high evaporation rate.

Eye: Moderate irritation from vapour. Irritation and possible freezing if liquid enters the eye.

Skin: Liquid can cause irritation and frostburn if in contact with skin.

Inhaled: May cause irritation to respiratory tract. Moderate exposure may cause headaches or dizziness.

Elevated exposure may cause unconsciousness and respiratory arrest.

By diluting the oxygen concentration in air below the level necessary to support life; it can act as an asphyxiant.

Effects of oxygen deficiency are:

16%: breathing and pulse rate increased, impaired thinking and attention, reduced coordination;

14%: Abnormal fatigue upon exertion, emotional upset, faulty coordination, poor judgement;

12.5%: Very poor judgement and coordination, impaired respiration that can cause permanent hearing damage, nausea and vomiting;

below 10%: Inability to perform various movements, loss of consciousness, convulsions, and death.

Chronic:

Long term exposure to LPG has no known health effects.

Prolonged exposure to an oxygen deficient atmosphere (below 19% oxygen in air) may affect the heart and nervous system.

First Aid:

Inhalation:

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness.

Remove victim to uncontaminated area whilst wearing self-contained breathing apparatus.

Victim may not be aware of asphyxiation.

Keep victim warm and rested.



MATERIAL SAFETY DATA SHEET
Title: LIQUEFIED PETROLEUM GAS MATERIAL SAFETY DATA SHEET
Date of Issue: 1 October 2021
Date of Next Review: 1 October 2026

Call a doctor.
Apply artificial respiration if breathing stopped.

Advice to Doctor:

Advise doctor that victim has been exposed to an oxygen deficient atmosphere.

General:

Rescuers should not enter an oxygen deficient atmosphere without using self-contained full face positive pressure breathing equipment.

Rescue personnel should be aware of extreme fire hazard associated with L.P.G. rich atmospheres.

FIRE FIGHTING MEASURES:

Flammability:

Highly flammable gas at normal pressure and temperatures.

Fire/Explosion Hazard:

Liquid Petroleum Gas is a highly flammable gas.

Exposure to fire may cause container to rupture/explode.

Cylinders involved in a fire/explosion may rocket.

Move cylinders from vicinity of fire if safe to do so.

Cool cylinders by spraying flooding quantities of water from a protected location.

If unable to keep cylinders cool, evacuate area, minimum distance 200 meters.

Do not extinguish a leaking gas flame unless absolutely necessary.

Spontaneous/explosive re-ignition may occur.

Extinguish any other fire.

Extinguishing Media:

Water, Fog or Fine water spray

Hazchem Code: 2 YE

Recommended Protective Clothing:

Full chemical suit and breathing apparatus should be worn

ACCIDENTAL RELEASE MEASURES:

Personal Protection:

Personnel engaged in the movement of cylinders shall be provided with safety footwear, safety glasses and leather or PVC gloves.

Full cover overalls are recommended. In areas where equipment failure may cause an immediate high concentration of LPG, ensure adequate ventilation and have approved self-contained, full face respiratory equipment readily available for emergencies.



MATERIAL SAFETY DATA SHEET
Title: LIQUEFIED PETROLEUM GAS MATERIAL SAFETY DATA SHEET
Date of Issue: 1 October 2021
Date of Next Review: 1 October 2026

Spills and Disposal:

Ventilate area. Stop leak if it can be done without risk. Allow gas to dissipate to atmosphere. Prevent from entering sewers, basements and work pits, or any place where its accumulation can be dangerous.

Reference Guide:

Standard SNZ HB 76:2008 Dangerous Goods – Initial Emergency Response Guide.
AS/NZS 1337 – Eye Protection for Industrial Applications
AS/NZS 2161.1 – Occupational Protective Gloves – Selection, use and maintenance
AS/NZS 1715 – Selection, Use and Maintenance of Respiratory Protective Devices
AS/NZS 1716 – Respiratory Protective Devices

General:

Only experienced and properly instructed personnel should handle compressed gases. Open valve slowly to avoid pressure shock. Cylinder contents and identification labels provided by the supplier must not be removed or defaced. Colour coding should not be the only criterion used for content identification.

HANDLING AND STORAGE:

Handling:

Flammability:

Highly flammable at normal temperatures and pressures.

General:

Only experienced and properly instructed personnel should handle compressed gases. Open valve slowly to avoid pressure shock. Cylinder contents and identification labels provided by the supplier must not be removed or defaced. Colour coding should not be the only criterion used for content identification.

Approved Handlers: Approved handlers are no longer required for this gas.

Approved Fillers: If you fill a compressed gas cylinder you must be an Approved Filler.

Storage:

Storage of compressed gas cylinders shall be in compliance with New Zealand HSNO Regulations.

Cylinders will be kept away from ignition sources (including static discharges).

Cylinders shall be stored in a cool, dry, well-ventilated area out of direct sunlight and away from heat and ignition sources.

No part of cylinders shall be exposed to temperatures above 50°C.



MATERIAL SAFETY DATA SHEET
Title: LIQUEFIED PETROLEUM GAS MATERIAL SAFETY DATA SHEET
Date of Issue: 1 October 2021
Date of Next Review: 1 October 2026

Cylinders shall be stored upright on a level, fireproof floor, secured in position and protected from damage.

Full cylinders shall be stored separately from empties.

Cylinders should be moved by hand-truck or cart designed for that purpose.

Separation:

Avoid any contact with oil or grease particularly to the cylinder valve.

Keep liquid petroleum gas cylinders a minimum of 5 meters away from ignition sources and from incompatible materials (e.g. HSNO classes 1, 3, 4 and 5).

Keep liquid petroleum gas cylinders a minimum of 5 meters away from edge of the controlled zone.

A controlled zone is an area surrounding a hazardous substance location, beyond the controlled zone members of the public are provided with reasonable protection from adverse events.

Spills and Disposal:

Ventilate area. Stop leak if it can be done without risk. Allow gas to dissipate to atmosphere. Prevent from entering sewers, basements and work pits, or any place where its accumulation can be dangerous.

EXPOSURE CONTROLS / PERSONAL PROTECTION:

Exposure Standards:

TWA 1000 ppm v/v STEL - Not applicable

Engineering Controls:

Provide ventilation to area of use to prevent accumulation of L.P.G. at flammable concentrations.

Provide adequate local exhaust and dilution (general) ventilation and supply sufficient replacement air to maintain oxygen concentration above 19%.

Personal Protection:

Personnel engaged in the movement of cylinders shall be provided with safety footwear, safety glasses and leather or PVC gloves.

Full cover overalls are recommended. In areas where equipment failure may cause an immediate high concentration of LPG ensure adequate ventilation and have approved self-contained, full face respiratory equipment readily available for emergencies.

Reference Guide:

AS/NZS 1337 – Eye Protection for Industrial Applications

AS/NZS 2161.1 – Occupational Protective Gloves – Selection, use and maintenance

AS/NZS 1715 – Selection, Use and Maintenance of Respiratory Protective Devices

MATERIAL SAFETY DATA SHEET

Title: LIQUEFIED PETROLEUM GAS MATERIAL SAFETY DATA SHEET
--

Date of Issue: 1 October 2021

Date of Next Review: 1 October 2026

AS/NZS 1716 – Respiratory Protective Devices

PHYSICAL AND CHEMICAL PROPERTIES:
--

Physical Properties

Appearance: Colourless, Odourless gas at room temperature. To detect gas leak, an odorant is added to the gas for early detection.

Flashpoint: -104 - 60°C

Boiling Point: -42°C

Flammability Limits: (In air) 1.8 – 9.5%

Vapour Pressure: Not Applicable

Solubility in Water : Not Applicable

Other Properties

Relative Density: (Air = 1): 1.47 – 2.08

Density of Gas: (101.3 kPa, 15°C): 1.80 - 2.55 kg/m³

Molecular Weight: 42 - 58

Critical Temperature: Not Applicable

STABILITY AND REACTIVITY:

Flammability:

Extremely flammable gas .

Materials Compatibility:

LPG is compatible with most common component materials.

However LPG is not combatable with Butyl (isobutene - isoprene) rubber (IIR), Silicon (Q), Chloroprene (CR),

Ethylene - Propylene (EPDM) and hydrocarbon based lubricants.

TOXICOLOGY INFORMATION:

LPG may cause irritation to respiratory tract. Moderate exposure may cause headaches or dizziness.



MATERIAL SAFETY DATA SHEET

Title: LIQUEFIED PETROLEUM GAS MATERIAL SAFETY DATA SHEET
--

Date of Issue: 1 October 2021

Date of Next Review: 1 October 2026

ECOLOGICAL INFORMATION:

No known ecological damage is caused by this product.

DISPOSAL CONSIDERATIONS:

Do not discharge into areas where there is a risk of forming an explosive mixture with air.

Waste gas should be flared through a suitable burner with flash back arrestor.

Do not discharge into any place where its accumulation could be dangerous.

TRANSPORT INFORMATION:

UN Number: 1075

Proper Shipping Name: LIQUEFIED PETROLEUM GAS

Dangerous Goods Class and Subsidiary Risk: 2.1

Packing Group: Not applicable

Hazchem Code: 2 YE

Other Information:

Avoid transport on vehicles where the load is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers:

Ensure that containers are firmly secured and upright (**Do not transport Acetylene cylinders laying down**)

Ensure cylinder valve is closed and not leaking.

Ensure there is adequate ventilation.

Compliance with applicable regulations.

REGULATORY INFORMATION:

Environmental Protection Agency Register Approval No: HSR001009

HSNO Controls:

Hazardous Substances (Classes 1 to 5 Controls) Regulations 2001.

Hazardous Substances (Disposal) Regulations 2001.

Hazardous Substances (Personnel Qualifications) Regulations 2001.

Hazardous Substances (Emergency Management) Regulations 2001.

Hazardous Substances (Identification) Regulations 2001.

Hazardous Substances (Compressed Gases) Regulations 2004.

Hazardous Substances (Tank Wagon and Transportable Containers) Regulations 2004.

Schedule 10 of the Hazardous Substances (Dangerous Goods and Scheduled Toxic



MATERIAL SAFETY DATA SHEET
Title: LIQUEFIED PETROLEUM GAS MATERIAL SAFETY DATA SHEET
Date of Issue: 1 October 2021
Date of Next Review: 1 October 2026

Substances) Transfer Notice 2004.
Schedule 12 of the Hazardous Substances (Dangerous Goods and Scheduled Toxic
Substances) Transfer Notice 2004

Approved Handlers: Approved handlers are no longer required for this gas.

Approved Fillers: If you fill a compressed gas cylinder you must be an Approved Filler.

OTHER INFORMATION:

Liquefied Petroleum Gas is supplied in low pressure cylinders specifically designed for LPG traffic.

Cylinder Colour:

Industrial: AS2700 –N24 (Silver Grey)

Cylinder Valve Outlet:

Industrial 45 kg Cylinder: AS 2473.2 Type 21.

Industrial Forklift Cylinder: AS2473.2 Type

References:

NZS 5433:2007 Transport of Dangerous Goods on Land

EPA Website – Approvals Register – www.epa.govt.nz

SNZ HB76:2008 Dangerous Goods – Initial Emergency Response Guide

AS1678 2C1 Emergency Procedure Guide – Transport – Non-Flammable, Compressed Gas

AS 4484-2004 - Gas Cylinders for Industrial, Scientific, medical and refrigerant use -

Labelling and colour coding

AS 2473.2-2007 - Valves for compressed gas outlets - Part 2 Outlet connections (threaded) and stem (inlet) threads

AS 2473.3-2007 - Valves for compressed gas outlets - Part 3 Outlet connections for medical gases (including pin-indexed yoke connections)

Operators Handbook for the Transport of Dangerous Goods by Road – NZ Road Transport & Logistics Industry Training Organisation

NZCIC Code of Practice – Preparation of Safety Data Sheets



MATERIAL SAFETY DATA SHEET
Title: LIQUEFIED PETROLEUM GAS MATERIAL SAFETY DATA SHEET
Date of Issue: 1 October 2021
Date of Next Review: 1 October 2026

MSDS SUMMARY:

This MSDS summarises to our best knowledge, at the date of issue, the health and safety hazard information regarding this product and general guidance on how to safely handle the product in the workplace. All due care has been taken to include accurate and up-to-date information in this MSDS.

Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Southern Gas Services Limited.

As far as lawfully possible, no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this MSDS can be accepted.

Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is available on request.

This MSDS has been prepared in accordance with NZCIC Code of Practice – Preparation of Safety Data Sheets.

This MSDS is subject to change without notice.